







PANASONIC FIRE ALARM SOLUTIONS
ACCESSORIES LIST
AE2010 Series
















DOCUMENT NAME:	ACCESSORIES LIST AE2010 Series
DOCUMENT NUMBER:	MEW01860
DATE OF ISSUE:	2016-02-19
REV:	-
DATE OF REVISION:	-



Panasonic Eco Solutions Nordic AB
Jungmansgatan 12
SE-211 19 Malmö
Sweden
Tel: +46 (0)40 697 70 00
E-mail: info.pesn@eu.panasonic.com
Internet: <http://pesn.panasonic.se>







ACCESSORIES LIST

Art. No.	Description	
PL 252	Plastic Pipe 4 meters, 25 mm An internal Ra value of 1.6 contributes to avoiding buildup of dust and bacteria in the pipeline, and to ensuring optimal functionality with respect to transportation of smoke.	
PL 253	Plastic Pipe 4 meters, 25 mm RED 25 mm plastic pipe	
PL 252 P 13 pieces	Plastic Pipe 4 meters, 25 mm 25 mm plastic pipe	
PL 253 P 13 pieces	Plastic Pipe 4 meters, 25 mm RED 25 mm plastic pipe	
AL 250	Pipe 4 meters, 25 mm Aluminium For use in environments with high temperatures, for example greenhouse.	
SK 252	Socket Extra long sleeve couplings with included sealant provide excellent connections in the pipeline and prevent pipes slipping apart.	

Art. No.	Description	Art. No.
SK 253	Socket RED For 25 mm plastic pipes.	
AL 250 S	Aluminium Socket For 25 mm aluminium pipes.	
BE 252	Bend, 90° Sleeve couplings bent at 90 degrees, including the same sealant as regular couplings.	
BE 253	Bend, 90° RED For 25 mm plastic pipes	
AL 250 B	Bend, 90° Aluminium For 25 mm aluminium pipes	
BE 252-45 A	Bend, 45° Sealant as in the standard bend. female/ female.	
BE 252-45 B	Bend, 45° female/male The "B" variant can be combined with "A" or the 90 degree bend to facilitate easy adaptation of the pipeline in twisting or difficult areas.	

Art. No.	Description	Art. No.
BE 253-45 A	Bend, 45° RED female/ female	
BE 253-45 B	Bend, 45° RED female/male The "B" variant can be combined with "A" or the 90 degree bend to facilitate easy adaptation of the pipeline in twisting or difficult areas.	
TG 250	T-off For branching of pipeline.	
TG 253	T-off RED For branching of pipeline.	
CL 250	Pipe Clips, 100 pieces Standard fastening clips for pipelines are quickly and easily mounted in the ceiling, and the pipes are then pressed into place.	
CL 253	Pipe Clips RED 100 pieces	

Art. No.	Description	
CL 250 W	Pipe Clips	
100 pieces	Fastening clips for wire suspension of pipelines. Silk wire is strung through the room, and the pipeline is pressed into the clips and pushed onto the wire from one end.	
CL 251 W	Pipe Clips for wire mounting	
100 pieces	Used among other for easy stretching of the pipe in greenhouses.	
CL 255	Pipe Clips Nylon	
100 pieces	For use in environments with large variations in temperature.	
SN 253 P	Sniffer 3 meter sampling point	
	The Sniffer may be used where it is desirable to conceal the pipeline (for example in churches) and/or there is a need for protection against insects, such as in greenhouses. The sniffer can also be drawn into fuse boxes, server racks and such, to achieve optimal detection in critical spots.	
SN 258 M	Sniffer 0.75 meter sampling point	
		
FI 003 KP	Filter Set, 5 pcs	
	Progressive filters prevent dust from contaminating the sensors. Comes complete with frames for quick and easy replacement.	
FI 004 KP	Filter Set, 5 pcs	
	White filter	

Art. No.	Description	
GG 006	Gartner 0.4 meter extension	
	Used in greenhouses with great distance from ridge and down to the heat / shadow curtains (<2.20 meter)	
GG 256	Gartner 0.8 meter sampling point	
	80 cm pipe branch for extended sampling points. Used for simple detection both over and underneath heat / shadow curtains in greenhouses.	
ELOCUT	Pipe Cutter	
	Elotecs pipes are delivered in 4 meter segments that may be cut to length where needed. To ensure clean cuts with no burrs, use the ELOCUT cutting tool.	
ELOVAC	Manometer	
	The manometer Elovac measures the vacuum in the outermost hole in the pipeline to verify the pipeline suction.	
EP 250	End Cap	
	Used to seal the end of the pipe to avoid foreign objects in the pipe. Used for pipe penetration in walls to avoid foreign objects in the pipe.	
AU 002	Exhaust Kit	
	Used to lead exhaust air back into rooms with large under pressure. Can also reduce fan noise or avoid the spread of odors if an Aspect installed in an office environment samples air from livestock rooms or similar. The exhaust kit is easily installed without tools. Just set the kit into the slot in the exhaust port, and push until it snaps into place. If the kit needs to be removed, one of the "keys" located inside the Aspect bottom cover may be used to release the snap. The AU 002 is then easily pulled free.	

Art. No.	Description	
FS 2010	Filter Box Complete with front piece, clip and filter elements.	
KG 250	Cross For branching of pipeline in large open areas where the pressure is the same in all pipes.	
KM 250 com	Adhesive markers for plastic pipe Placed on pipeline for highlighting holes. Markers must be positioned so that it surrounds the hole and points in the Aspect direction.	
LK 501	Condense Bottle with UV-stabiliser Installed before Aspect to remove condensation from the sampled air before it enters the detection chamber.	
VF 250 com	Vulcan Cyclone Filter Install the VULCAN in front of Aspect to remove both dust and condensation from the sampled air before it enters the detection chamber. Used when securing rooms with extreme amounts of dust. The VULCAN has been carefully designed not to increase transport time by more than five seconds. The VULCAN should be installed immediately before pipe entry into Aspect. NOTE! It is important to connect the VULCAN to earth to avoid static build-up that will affect the performance of the filter.	
PLP 210 007	HUB for Aspect, 2-1 Used to merge the two pipelines of the Aspect if only one pipeline is used.	

Art. No.	Description
----------	-------------

BA 700	12V 7 Ah Battery
--------	------------------

	Standard battery for Aspect.
--	------------------------------



TA010P	Test bottle for Aspirating detectors, 10 pcs
--------	--

	Bottle with test smoke in the form of titanium tetrachloride to test the functionality of the system.
--	---



PH12-36B	PowerHouse, Battery Box
----------	-------------------------

	Elotec Powerhouse is a 12V battery cabinet. This battery cabinet is designed for use with Aspects internal power supply. The cabinet has IP44 protection class.
--	---



Elopad2	5" Android Tablet
---------	-------------------

	Used with the app ASPECT TOOL and diagnose WiFi module for information, programming, and services of the Aspect.
--	--



DIAMANT	Diamant Filter guard protection
---------	---------------------------------

	Module for protecting the filter guard inside the Aspect. Supplied in kit with necessary hoses for different modules of Elotec aspirating detectors.
--	--

	DIAMANT is replaced by annual checks or when needed. Accumulated detritus are clearly visible in front.
--	---

